查询TMG5C80D供应商

TRIAC(Surface Mount Device / Non-isolated)

TMG5C80D

SanRex Triac **TMG5C80D** is designed for full wave AC control applications. It can be used as an ON/OFF function or for phase control operation.

Typical Applications

- Home Appliances : Washing Machines, Vacuum Cleaners, Rice Cookers, Micro Wave Ovens, Hair Dryers, other control applications
- Industrial Use : SMPS, Copier Machines, Motor Controls, Dimmer, SSR, Heater Controls, Vending Machines, other control applications

Features

- $I_{T(RMS)}$=5A
- High Surge Current
- Low Voltage Drop
- Lead-Free Package

TO-252



Identifying Code : T5C8D Unit : mm

■Maximum Ratings

(Tj=25℃ unless otherwise specified)

Symbol	Item	Reference	Ratings	Unit
V_{DRM}	Repetitive Peak Off-State Voltage		800	V
$I_{T(RMS)}$	R.M.S. On-State Current	Tc=107℃	5	A
I_{TSM}	Surge On-State Current	One cycle, 50Hz/60Hz, Peak value non-repetitive	50/55	A
I^2t	I^2t (for fusing)		12.6	A^2S
P_{GM}	Peak Gate Power Dissipation		3	W
$P_{G(AV)}$	Average Gate Power Dissipation		0.3	W
I_{GM}	Peak Gate Current		2	A
V_{GM}	Peak Gate Voltage		10	V
Tj	Operating Junction Temperature		−40～+125	℃
Tstg	Storage Temperature		−40～+150	℃
	Mass		0.32	g

■Electrical Characteristics

Symbol		Item	Reference	Ratings			Unit
				Min.	Typ.	Max.	
I_{DRM}		Repetitive Peak Off-State Current	V_D=V_{DRM}, Single phase, half wave, Tj=125℃			1	mA
V_{TM}		Peak On-State Voltage	I_T=7A, Inst. measurement			1.4	V
I_{GT1}^{+}	1	Gate Trigger Current	V_D=6V, R_L=10Ω			20	mA
I_{GT1}^{-}	2					20	
I_{GT3}^{+}	3					—	
I_{GT3}^{-}	4					20	
V_{GT1}^{+}	1	Gate Trigger Voltage				1.5	V
V_{GT1}^{-}	2					1.5	
V_{GT3}^{+}	3					—	
V_{GT3}^{-}	4					1.5	
V_{GD}		Non-Trigger Gate Voltage	Tj=125℃, V_D=½V_{DRM}	0.2			V
(dv/dt)c		Critical Rate of Rise of Off-State Voltage at Commutation	Tj=125℃, (di/dt)c=−2.5A/ms, V_D=400V	5			V/μs
I_H		Holding Current			10		mA
Rth(j-c)		Thermal Resistance	Junction to case			3.0	℃/W

Trigger mode of the triac



Gate Characteristics



On-State Characteristics (MAX)



RMS On-State Current vs Maximum Power Dissipation



RMS On-State vs Allowable Case Temperature



Surge On-State Current Rating (Non-Repetitive)



Transient Thermal Impedance



IGT —Tj (Typical)



VGT —Tj (Typical)